



# Waterproof Fan

Turning the Axis of the Word!

Specialist in Thermal Solution System



PRODUCTS ARE ROHS/LEAD-FREE COMPLIANCE.

FONTEK CO., LTD. TEL : 886 2 26592598 FAX : 886 2 26592798 support.tw@fontekcorp.com



ISO 9001:2008  
QS-9000:1999  
CERTIFICATE  
No A8935

Bearing type: ☉=Ball ※=Sleeve ○=1B1S ●=Hypro Bearing

FRAMESIZE	MODEL NO	BEARING	Voltage	CURRENT	POWER	Speed	Maximum AirFlow		Maximum Pressure		NOISE	WEIGHT
			(VDC)	(A)	(W)	(RPM)	(CMM)	(CFM)	(InAq)	(mmAq)	(dB/A)	(g)
60x60x25	AQ0612LB-A70GL(T)	☉	12	0.07	0.84	2500	0.37	13.20	0.06	1.60	18.1	68
60x60x25	AQ0612MB-A71GL(T)	☉	12	0.10	1.20	3500	0.51	18.18	0.12	3.10	28.6	68
60x60x25	AQ0612HB-A71GL(T)	☉	12	0.16	1.92	4500	0.69	24.48	0.20	5.08	35.2	68
60x60x25	AQ0612UB-A71GL(T)	☉	12	0.19	2.28	5000	0.76	27.00	0.23	5.84	40.0	68
60x60x25	AQ0624HB-A70GL(T)	☉	24	0.12	2.88	4500	0.69	24.48	0.20	5.08	35.2	68
60x60x25	AQ0624UB-A71GL(T)	☉	24	0.14	3.36	5000	0.76	27.00	0.23	5.84	40.0	68
FRAMESIZE	MODEL NO	BEARING	Voltage	CURRENT	POWER	Speed	Maximum AirFlow		Maximum Pressure		NOISE	WEIGHT
			(VDC)	(A)	(W)	(RPM)	(CMM)	(CFM)	(InAq)	(mmAq)	(dB/A)	(g)
70x70x25	AQ0712LB-A70GL(T)	☉	12	0.10	1.20	3300	0.80	28.20	0.15	3.81	31.6	61
70x70x25	AQ0712MB-A70GL(T)	☉	12	0.12	1.44	3800	0.91	32.30	0.18	4.47	33.6	61
70x70x25	AQ0712HB-A70GL(T)	☉	12	0.18	2.16	4200	1.01	35.50	0.22	5.51	38.0	61
FRAMESIZE	MODEL NO	BEARING	Voltage	CURRENT	POWER	Speed	Maximum AirFlow		Maximum Pressure		NOISE	WEIGHT
			(VDC)	(A)	(W)	(RPM)	(CMM)	(CFM)	(InAq)	(mmAq)	(dB/A)	(g)
80x80x25	AQ0812LB-A70GL(T)	☉	12	0.08	0.96	2100	0.77	27.02	0.07	1.78	22.3	86
80x80x25	AQ0812MB-A70GL(T)	☉	12	0.12	1.44	2500	0.92	32.38	0.10	2.54	29.4	86
80x80x25	AQ0824LB-A70GL(T)	☉	24	0.04	0.96	2100	0.77	27.02	0.07	1.78	22.3	86
80x80x25	AQ0824MB-A70GL(T)	☉	24	0.07	1.68	2500	0.92	32.38	0.10	2.54	29.4	86
FRAMESIZE	MODEL NO	BEARING	Voltage	CURRENT	POWER	Speed	Maximum AirFlow		Maximum Pressure		NOISE	WEIGHT
			(VDC)	(A)	(W)	(RPM)	(CMM)	(CFM)	(InAq)	(mmAq)	(dB/A)	(g)
92x92x25	AQ0912LB-A70GL(T)	☉	12	0.10	1.20	2100	1.15	40.69	0.08	2.06	29.2	92
92x92x25	AQ0912MB-A70GL(T)	☉	12	0.15	1.80	2400	1.26	44.66	0.10	2.57	31.2	92
FRAMESIZE	MODEL NO	BEARING	Voltage	CURRENT	POWER	Speed	Maximum AirFlow		Maximum Pressure		NOISE	WEIGHT
			(VDC)	(A)	(W)	(RPM)	(CMM)	(CFM)	(InAq)	(mmAq)	(dB/A)	(g)
120x120x25	AQ1212DB-A71GL(N)	☉	12	0.11	1.32	1500	1.62	57.21	0.07	1.88	27.2	156
120x120x25	AQ1212LB-A71GL(N)	☉	12	0.15	1.80	1800	2.03	71.81	0.09	2.36	34.3	156
120x120x25	AQ1212MB-A71GL(N)	☉	12	0.16	1.92	2050	2.30	81.05	0.11	2.87	38.0	156
120x120x25	AQ1212HB-A71GL(N)	☉	12	0.29	3.48	2200	2.49	87.87	0.13	3.40	39.1	156
120x120x25	AQ1224DB-A71GL(N)	☉	24	0.06	1.44	1500	1.62	57.21	0.07	1.88	27.2	156
120x120x25	AQ1224LB-A71GL(N)	☉	24	0.08	1.92	1800	2.03	71.81	0.09	2.36	34.3	156
120x120x25	AQ1224MB-A71GL(N)	☉	24	0.11	2.64	2050	2.30	81.05	0.11	2.87	38.0	156
120x120x25	AQ1224HB-A71GL(N)	☉	24	0.13	3.12	2200	2.49	87.87	0.13	3.40	39.1	156
FRAMESIZE	MODEL NO	BEARING	Voltage	CURRENT	POWER	Speed	Maximum AirFlow		Maximum Pressure		NOISE	WEIGHT
			(VDC)	(A)	(W)	(RPM)	(CMM)	(CFM)	(InAq)	(mmAq)	(dB/A)	(g)
120x120x38	AQ1212DB-F51(FN)	☉	12	0.11	1.32	1500	1.62	57.29	0.09	2.16	28.4	290
120x120x38	AQ1212LB-F51(FN)	☉	12	0.19	2.28	1950	2.03	71.64	0.13	3.25	36.2	290
120x120x38	AQ1212MB-F51(FN)	☉	12	0.33	3.96	2540	2.73	96.30	0.23	5.79	45.0	290
120x120x38	AQ1212HB-F51(FN)	☉	12	0.45	5.40	2800	2.99	105.46	0.27	6.73	46.7	290
120x120x38	AQ1224DB-F51(FN)	☉	24	0.08	1.92	1500	1.62	57.29	0.09	2.16	28.4	290
120x120x38	AQ1224LB-F51(FN)	☉	24	0.12	2.88	1950	2.03	71.64	0.13	3.25	36.2	290
120x120x38	AQ1224MB-F51(FN)	☉	24	0.19	4.56	2540	2.73	93.30	0.23	5.79	45.0	290

<b>120x120x38</b>	AQ1224HB-F51(FN)	©	24	0.24	5.76	2800	2.99	105.46	0.27	6.73	46.7	290
<b>120x120x38</b>	AQ1248LB-F51(FN)	©	48	0.06	2.88	1950	2.03	71.64	0.13	3.25	36.2	290
<b>120x120x38</b>	AQ1248MB-F51(FN)	©	48	0.10	4.80	2540	2.73	96.30	0.23	5.79	45.0	290
<b>120x120x38</b>	AQ1248HB-F51(FN)	©	48	0.18	8.64	2800	2.99	105.46	0.27	6.73	46.7	290